

Dynaudio quality, tailored for you

Dynaudio Custom Performance in-wall speakers are super-shallow for tight cavities, and are optimised for wide dispersion

Performance series

In-wall






DYNAUDIO

Performance series

In-wall

- 2-way systems
- Ranging from 5 in to 8 in
- EQ adjustment for the tweeter
- Magnetic paintable grilles
- Shallow depth for tight cavities
- MSP (Magnesium Silicate Polymer) woofer cone
- 1 in coated soft-dome tweeters

Model number	P4-W65	P4-W80	P4-LCR50
			
Type	2-way in-wall	2-way in-wall	2-way in-wall
Drivers	Tweeter: 28 mm (1 in); mid/bass: 165 mm (6½ in)	Tweeter: 28 mm (1 in); mid/bass: 200 mm (8 in)	Tweeter: 28 mm (1 in); mid/bass: 2x130 mm (5 in)
Performance frequency response (+/- 3 dB)	46 Hz–20 kHz	42 Hz–20 kHz	46 Hz-20 kHz
Impedance (nominal/minimum)	8 Ω / 5 Ω	8 Ω / 5 Ω	4 Ω / 3.2 Ω
Sensitivity (dB SPL [2.83 V/1m])	87.5 dB	89.0 dB	89 dB
Continuous power*	40 W	50 W	50 W
Long-term power*	80 W	160 W	100 W
Tweeter-level options	-3 dB, 0 dB +3 dB	-3 dB, 0 dB +3 dB	+3 dB,0 dB,-3 dB
Dimensions (W x H x D)	198 x 296 mm x 63 mm (7¾ x 11¹¹⁄₁₆ in x 2½ in)	237 x 392 mm x 77 mm (9⁵⁄₁₆ x 15¾ in x 3 in)	360 x 195 mm x 77 mm (14¼ in x 7¾ in x 3 in)
Cut-out dimensions	175 x 275 mm (6⅞ x 10⅞ in)	215 x 370 mm (8½ x 14½ in)	175 x 340 mm (6⅞ in x 13⅜ in)
Grille options	Rectangular	Rectangular	Rectangular

* Measured according to IEC 60268-5 using a pink noise input signal. Continuous is 100 h operation.
Long Term is 10 cycles of 1 min. On and 2 min. Off.